



- PRACTICAL** : Digital display of voltage and current.
- PRECISE** : Coarse and fine voltage adjustment.
- Adjustable current from 0 to 5A or 0 to 1A .
- USEFUL** : Automatic constant voltage or current operation.
- PROTECTED** : Short circuit protection.



150 WATTS
0 - 30 V 0 - 5 A



Specifications

Voltage

- Floating outputs on 4 mm safety terminals.
- Automatic constant voltage operation.
- Adjustable from 0 to 30 V (0 to + or -5 mV) with fine adjustment (about 2,5 Volts).
- Regulation : < 20 mV for a load variation from 0 to 100%.
 < 15 mV for a 10% line variation.
- Ripple : < 3 mV peak to peak or 1 mV rms.
- Internal resistance : < 4 mΩ.
- Indicators : green LED for voltage regulation.
- Display : 14 mm 3 digit LED digital voltmeter.
- Resolution : 100 mV.

Current

- Automatic constant current operation.
- Two selectable current ranges : 5 A or 1 A.
- Adjustable from 0 to 5 A or from 0 to 1 A, depending on the selected range.
- Regulation : < 10 mA for a 10% line change.
 < 15 mA for a load change from 0 to 100%.
- Ripple : < 6 mA peak to peak or 2,1 mA rms.
- Indicators : red LED for current regulation.
- Display : 14 mm 3 digit LED digital ammeter.
- Resolution : 10 mA.

Protection

- Short circuit protection, by current regulation.
- Overtemperature protection, by thermal circuit-breaker and by relay on the transformer.
- Transformer primary overcurrent protection, by fuse.

Other specifications

- Safety : Class I, enhanced safety between mains input and outputs. Complies with EN 61010-1, overvoltage category II, pollution degree 2.
- EMC : Complies with EN 61326-1, performance criteria B, and EN 55011, ISM Group I, Class B.
- Input voltage : 230 V ±10%, 50/60 Hz.
- Mains input : Socket C14 with C13 removable cable (2 poles + earth).
- Power consumption : 315 VA.
- Dielectric strength : 2300 V from input to output, 1350 V from input to chassis.
- Outputs : safety terminals (VDE 0110 standard and BG certified), and safety inverted earth terminal.
- Presentation : screen-printed polycarbonate front panel, metal case, epoxy finish.