

EAN CODE : 3760244880246

12 V REMOTE SENSING



ALE1202

- PRECISE** : Output ripple < 3 mV rms.
- Remote sensing to overcome voltage drop in the power lines.
- PRACTICAL** : Output voltage adjustable from 10 to 15 V.
- Spring terminal block.
- PROTECTED** : Short circuit protection.
- EASY** : Direct DIN rail or panel mounting.



30 WATTS

12 V (Adj. 10 to 15 V)
2,5 A



Specifications

Voltage

- Floating outputs on spring terminal block for 2,5 mm² (AWG12) wires
- Output voltage : adujstable from 10 to 15 V.
- Regulation : <25 mV for a load variation from 0 to 100%
5 mV for a line variation from -10 to +10%
- Ripple : < 3 mV rms including :
3 mV peak to peak of the signal at 65 kHz
< 4 mV peak to peak of the signal at 100 Hz
< 35 mV peak to peak of switching spikes
- Hold-up time : 50 ms at full load (230 V line input)
- Indicator : green power-on LED indicator

Current

- Max I : 3 A at 10 V
2,5 A at 12 V
2 A at 15 V

Power

- Max output power : 30 W

Protections

- Against short-circuits by circuit breaker with automatic reset
- Against transients on the primary circuit by varistor
- Against overcurrent on primary circuit by fuse

Remote sensing

- Correction of the voltage drop in the wires (4 wires method)
- Input on disconnect scribe terminal blocks for 2,5 mm² wires (AWG12)
- Correction : Max 3 V (1,5 V per wire)
- Ripple : < 30 mV for a load variation from 0 to max.

Other specifications

- Safety : Class II, Safety Extra Low Voltage (SELV),
complies with EN 61010-1, EN 61010-2-201 and EN 61368-1.
- EMC : Complies with EN 61000-6-2 and EN 61000-6-4.
- Overvoltage Category : II ; Pollution Degree : 2.
- Installation altitude : < 2000 m.
- Protection level : IP30
- Operating temperature : from -25 °C to +70 °C
Derating : 1 W/°C from +55 °C
- Input voltage : 190 to 264 V, 50-60 Hz
- Mains input : disconnect scribe terminal blocks for 2,5 mm² wires (AWG12)
- Power consumption : max 35 W
- Dielectric strength : 3000 VAC from input to output
- Presentation : polycarbonate modular case (3 modules) screenprinted
- Dimension : 54 x 95 x 58 mm (lxhxp)
- Mounting : Clipspackage integrated in modular case for DIN rail profile 35x7,5 mm or 35x15 mm removable wall mounting integrated case to the 4 mm screws.

