

EAN CODE :3760244880239

$\pm 15\text{ V}$  or  $12\text{ V}$  or  $24\text{ V}$



ALE1502D



- PRECISE :** Switching power supply offering a ripple < 3 mV rms.
- Output voltage adjustable from  $\pm 10$  to  $\pm 15\text{ V}$
- SMALL :** Modular,
- EASY :** direct DIN rail or panel mounting
- PROTECTED :** against short circuits and reverse polarity.
- RESISTANT TO SHOCK**

## 60 WATTS

$\pm 10$  to  $15\text{ V } 2\text{ A}$   
or  $12\text{ V } 5\text{ A}$   
or  $24\text{ V } 2\text{ A}$



## Specifications

- Floating outputs on spring terminal block with levers for 2,5 mm<sup>2</sup> (AWG 12) wires.
- Balanced-output voltage adjustable from  $\pm 10$  to  $\pm 15\text{ V}$

### +15 V output

- Regulation : < 20 mV for a load variation from 0 to 100%.  
< 2 mV for a line variation from -10 to +10%.
- Ripple : < 3 mV rms including :  
< 3 mV peak to peak of the signal at 100 kHz  
< 5 mV peak to peak of the signal at 100 Hz  
< 12 mV peak to peak of switching spikes

### -15 V output

- Regulation : < 20 mV for a load variation from 0 to 100%.  
< 2 mV for a line variation from -10 to +10%.
- Ripple : < 3 mV rms including :  
< 4 mV peak to peak of the signal at 330 kHz  
< 4 mV peak to peak of the signal at 100 Hz  
< 15 mV peak to peak of switching spikes

### 24V Output (Adjustable from 20 to 30V)

Available between output + and -

- Regulation : < 35 mV for a load variation from 0 to 100%  
< 10 mV for a line variation from -10 to +10%.
- Ondulation : < 3 mV rms including:  
< 8 mV peak to peak of the switching signal  
< 5 mV peak to peak of the signal at 100 Hz  
< 15 mV peak to peak of switching spikes.

### Indicators

- Green power-on LED indicator.
- Overheat or overcurrent red LED "status" indicator

### Current +15 V (alone)

- I max : 5,5 A in short circuit condition  
5 A from 10 to 12 V ; 4 A at 15 V

### Current -15 V (alone)

- I max : 2,1 A in short-circuit condition  
2 A from 10 to 15 V

### Current 24V (Adjustable from 20 to 30 V)

- I max : 2,1 A in short-circuit condition  
2 A from 20 to 30 V

### Power

- Max output power : 60 W.
- I max  $\pm 15\text{ V}$  : 2 A

### Protections

- Against short-circuits by current limit.
- Against overcurrent on primary circuit by fuse.
- Against overtemperature, by thermal shutdown.
- Cover on input output terminal block.

## Other specifications

- Safety : Class II, Safety Extra Low Voltage (SELV), complies with EN 61010-1, EN 61010-2-201 and EN61368-1.
- EMC : Complies with EN 61000-6-2 and EN 61000-6-4.
- Overvoltage Category : II ; Pollution Degree : 2.
- Installation altitude : < 2000 m.
- Protection level : IP 30.
- Operating temperature : from -25 to +60 °C ; derating : 1 W/°C from +40 °C
- Input voltage : 190 to 264 Volts, 50-60 Hz.
- Mains input : spring terminal block with levers for 2,5 mm<sup>2</sup>, (AWG 12) wires.
- Power consumption : 78 W max.
- Dielectric strength : 3000 VAC from input to output.
- Presentation : modular polycarbonate case (6 x 17,5 mm) screenprinted.
- Mounting : Clips package integrated in modular case for DIN rails profile 35x7,5 mm or 35x15 mm.  
Removable wall mouting integrated to the case for 4 mm screws.