

EAN CODE : 3760244880192



24 V

ALF2401

- PRATICAL** : ON/OFF switch.
 - Power-on indicator.
- PRECISE** : Output ripple < 3 mV rms.
 - Output voltage adjustable from 20 to 30 V.
- PROTECTED** : against Short circuit.
- RESISTANT TO SHOCK**

**30 WATTS**

24 V (Adj. 20 to 30 V)
1,25 A

**Specifications****Voltage**

- Floating outputs on 4 mm safety sockets.
- Output voltage : adjustable from 20 to 30 V. Delivered to 24 V $\pm 1\%$
- Regulation : < 20 mV for a load variation from 0 to 100%
< 5 mV for a line variation from -10 to +10%.
- Ripple : < 3 mV rms including:
 - < 3 mV peak to peak of the switching signal
 - < 4 mV peak to peak of the signal at 100 Hz
 - < 15 mV peak to peak of switching spikes
- Dynamic regulation : < 0,5% for a load variation from 10 to 90%
- Indicator : green power-on LED indicator.

Current

- Max I : 1,5 A to 20 V
1,25 A to 24 V
1 A to 30 V

Power

- Max output power : 30 W.
- Efficiency : >82% at the full power (30 W in output)

Protection

- Against short circuit protection, by current limit.
- Against overcurrent on main input, by fuse.
- Against transient pulse on the primary by varistor.

Other specifications

- Safety : Class II, Safety Extra Low Voltage (SELV) according to EN 61010-1.
- EMC : Complies with EN 61326-1, performance criteria B, and EN 55011, ISM Group I, Class B.
- Protection level : IP 30.
- Input voltage : 190 to 264 Volts, 50/60 Hz.
- Mains input : C8 socket with CEI320 C7 removable cable (2 poles double insulation).
- Power consumption : 35 W max.
- ON/OFF control : toggle switch
- Dielectric strength : 3000 VAC between input and output.
- Presentation : polycarbonate case screenprinted.